



International Label # IN10009B

The following information must be imprinted centered on the label except for the Date Code -

- **Quantity** - When the quantity is one, the word “One” is used. If the quantity is greater than one, the numeral is to be used. (Font: Arial / Size:16)
- **Description** – Short Description of the Part (Font: (Arial Black / Size 12)
- **Country of Origin** – Products manufactured outside of the USA are required to include “Made in (country)”. Products manufactured within the USA should state “Assembled in USA”. (Font Arial / Size 10)
- **Date Code** – Where the first digit, B, is the month (A-January, B=February, C=March, etc.), 25 is the designation for the last digits of the year (26=2026, 27=2027, etc.) and the last digit V is a fixed variable that is currently defined as V. (Font: Arial / Size 16)
- **Part Number** – International Part Number (Font: Arial Black / Size 20)
- **Bar Code** – Must include Bar Code 39 and when scanned only reads our International Part Number (No prefixes or suffixes)



Typical Technical Value

Face	Transfer Premium Extra -FCS	
Product	Matte-coated, lignin free label paper	
Substance weight	40lbs/ream (25"x38")	TAPPI-410
Caliper	2,8mil	TAPPI-411
Tensile strength MD	16 lbf/in	TAPPI-494
Tensile strength CD	16 lbf/in	TAPPI-494
Brightness	87%	TAPPI-452
Opacity	85%	TAPPI-425
Sustainability	The product is sold as FSC Mix Credit under FSC™ certificate.	
Backing	40# WHITE KRAFT	
Product	White kraft liner.	
Use	For roll-to-roll applications and photocell dispensing	
Substance weight	42 lbs./ream (24"x36")	TAPPI-410
Caliper	2.4 mil	TAPPI-494
Tensile strength MD	40lbf/in	TAPPI-494
Tensile strength CD	18lbf/in	TAPPI-494
Opacity	61%	TAPPI-425

Adhesive	
Type	Permanent
Composition	Waterborne acrylic
Use	Good adhesion to all standard substrates, including non-polar surfaces, films and corrugated board. Good low temperature performance.
Tack	19N; FTM 9
Minimum labelling temperature	32°F
Service temperature minimum	-4°F
Service temperature max	176°F
Performance	
Total substance	99lbs. /ream (25" x 38") Total
Caliper	5.5 mil